

TECHNICAL SPECIFICATIONS FOR **ERGODRIVE LET-OFF** INSTALLATION

SMIT - NUOVO PIGNONE loom specs

CUSTOMER:

.....

.....

.....

.....

AGENT:

.....

.....

.....

.....

LOOM: **SMIT - NP** YEAR: SERIAL N°:

TYPE:		VERSION:		LOOM WIDTH:		
<input type="checkbox"/> TP300	<input type="checkbox"/> TP400	<input type="checkbox"/> Dobby		<input type="checkbox"/> 190	<input type="checkbox"/> 200	<input type="checkbox"/> 210
<input type="checkbox"/> TP500		<input type="checkbox"/> Jacquard STÄUBLI JC4		<input type="checkbox"/> 220	<input type="checkbox"/> 230	<input type="checkbox"/> 240
<input type="checkbox"/> TP600		<input type="checkbox"/> Jacquard STÄUBLI JC5		<input type="checkbox"/> 250	<input type="checkbox"/> 260	<input type="checkbox"/> 270
<input type="checkbox"/> FAST P		<input type="checkbox"/> Jacquard BONAS IBJ2		<input type="checkbox"/> 280	<input type="checkbox"/> 290	<input type="checkbox"/> 300
<input type="checkbox"/> FAST R		<input type="checkbox"/> Jacquard GROSSE EJP-2HS		<input type="checkbox"/> 320	<input type="checkbox"/> 330	<input type="checkbox"/> 340
<input type="checkbox"/> FAST S				<input type="checkbox"/> 360	<input type="checkbox"/> 380	<input type="checkbox"/> 400
3PH POWER SUPPLY:	 V	<input type="checkbox"/> 50 Hz	<input type="checkbox"/> 60 Hz		
LOOM SPEED RPM:		MIN.	MAX.			
WEFT DENSITY /CM:		MIN. PPCM	MAX. PPCM	/INCH:	MIN. PPI	MAX. PPI
PREFERRED WEFT DENSITY /CM:		MIN. PPCM	MAX. PPCM	/INCH:	MIN. PPI	MAX. PPI
YARN TYPE:	<input type="checkbox"/> COTTON	<input type="checkbox"/> WOOL	<input type="checkbox"/> PURE SILK	<input type="checkbox"/> SYNTHETIC	<input type="checkbox"/> POLYPROPYLENE	<input type="checkbox"/> other
WARP COUNT:		from		to		
WEFT COUNT:		from		to		
N° OF WARP ENDS:				MAX. TENSION PER END cN:		
WEAVING PATTERN:		<input type="checkbox"/> 1/1	<input type="checkbox"/> 2/1	<input type="checkbox"/> 3/1	<input type="checkbox"/> 4/1	<input type="checkbox"/>
EXISTING WARP LET-OFF:		<input type="checkbox"/> Mechanical	<input type="checkbox"/> STROMAG	<input type="checkbox"/> BERGER LAHR	<input type="checkbox"/> other	
WHIPROLL:		<input type="checkbox"/> NORMAL	<input type="checkbox"/>			
DIFFERENTIAL:		<input type="checkbox"/> WITH		<input type="checkbox"/> WITHOUT		
No. PINION TEETH:		<input type="checkbox"/> 15	<input type="checkbox"/> 16	<input type="checkbox"/>		
No. W. BEAM WHEEL TEETH:		<input type="checkbox"/> 121	<input type="checkbox"/> 162	<input type="checkbox"/>		
SCREW/SPROCKET RATIO:		<input type="checkbox"/> 1:60	<input type="checkbox"/>			
WARP BEAM FLANGE MM:		<input type="checkbox"/> 600	<input type="checkbox"/> 700	<input type="checkbox"/> 800	<input type="checkbox"/> 940	<input type="checkbox"/> 1000 <input type="checkbox"/> 1016
BEAM BARRELL MM:		<input type="checkbox"/> 140	<input type="checkbox"/> 150	<input type="checkbox"/> 160	<input type="checkbox"/> 190	<input type="checkbox"/> 216 <input type="checkbox"/> 270