

TECHNICAL SPECIFICATIONS FOR **ERGODRIVE** INSTALLATION
SULZER RÜTI loom specs

CUSTOMER:
.....
.....
.....
.....

AGENT:
.....
.....
.....
.....

LOOM: **SULZER RÜTI** YEAR: SERIAL N°:

TYPE:		VERSION:		LOOM WIDTH:	
<input type="checkbox"/> F2000	<input type="checkbox"/> Tappet cams	<input type="checkbox"/> 170	<input type="checkbox"/> 180		
<input type="checkbox"/> F2001	<input type="checkbox"/> Dobby	<input type="checkbox"/> 190	<input type="checkbox"/> 200		
<input type="checkbox"/> G6100	<input type="checkbox"/> Automatic dobbie	<input type="checkbox"/> 210	<input type="checkbox"/> 220		
<input type="checkbox"/> G6200	<input type="checkbox"/> Jacquard	<input type="checkbox"/> 230	<input type="checkbox"/> 240		
		<input type="checkbox"/> 250	<input type="checkbox"/> 260		
3PH POWER SUPPLY:	 V	<input type="checkbox"/> 50 Hz	<input type="checkbox"/> 60 Hz	
LOOM SPEED RPM:		MIN.	MAX.		
WEFT DENSITY /CM:		MIN. PPCM	MAX. PPCM	/INCH:	MIN. PPI MAX. PPI
PREFERRED WEFT DENSITY /CM:		MIN. PPCM	MAX. PPCM	/INCH:	MIN. PPI MAX. PPI
YARN TYPE:	<input type="checkbox"/> COTTON	<input type="checkbox"/> WOOL	<input type="checkbox"/> PURE SILK	<input type="checkbox"/> SYNTHETIC	<input type="checkbox"/> POLYPROPYLENE <input type="checkbox"/> other
WARP COUNT:		from to			
WEFT COUNT:		from to			
N° OF WARP ENDS:			MAX. TENSION PER END cN:		
WEAVING PATTERN:		<input type="checkbox"/> 1/1	<input type="checkbox"/> 2/1	<input type="checkbox"/> 3/1	<input type="checkbox"/> 4/1 <input type="checkbox"/>
EXISTING WARP LET-OFF:		<input type="checkbox"/> SULZER Mechanical	<input type="checkbox"/> SULZER Electronic	<input type="checkbox"/> other	
WHIPROLL:		<input type="checkbox"/> NORMAL		<input type="checkbox"/> WITH TORSION BAR	
DIFFERENTIAL:		<input type="checkbox"/> WITH		<input type="checkbox"/> WITHOUT	
No. PINION TEETH:		<input type="checkbox"/> only for G6100/G6200			
No. W. BEAM WHEEL TEETH:		<input type="checkbox"/>			
SCREW/SPROCKET RATIO:		<input type="checkbox"/> 1:48 for F2000/F2001		<input type="checkbox"/> 1:117 for G6100/G6200	
WARP BEAM FLANGE MM:		<input type="checkbox"/> 600	<input type="checkbox"/> 700	<input type="checkbox"/> 800	<input type="checkbox"/> 940 <input type="checkbox"/> 1000
BEAM BARRELL MM:		<input type="checkbox"/> 140	<input type="checkbox"/> 150	<input type="checkbox"/> 216	<input type="checkbox"/> 262 <input type="checkbox"/> 270