

TECHNICAL SPECIFICATIONS FOR **ERGODRIVE** INSTALLATION

**SULZER RÜTI loom specs**

CUSTOMER: .....  
.....  
.....  
.....  
.....

AGENT: .....  
.....  
.....  
.....  
.....

LOOM: **SULZER RÜTI** YEAR: .....

SERIAL N°: .....

TYPE:		VERSION:		LOOM WIDTH:	
<input type="checkbox"/> F2000	<input type="checkbox"/> Tappet cams	<input type="checkbox"/> 170	<input type="checkbox"/> 180		
<input type="checkbox"/> F2001	<input type="checkbox"/> Dobby	<input type="checkbox"/> 190	<input type="checkbox"/> 200		
<input type="checkbox"/> G6100	<input type="checkbox"/> Automatic dobbie	<input type="checkbox"/> 210	<input type="checkbox"/> 220		
<input type="checkbox"/> G6200	<input type="checkbox"/> Jacquard	<input type="checkbox"/> 230	<input type="checkbox"/> 240		
		<input type="checkbox"/> 250	<input type="checkbox"/> 260		
<b>3PH POWER SUPPLY:</b>		..... V	<input type="checkbox"/> 50 Hz	<input type="checkbox"/> 60 Hz	
<b>LOOM SPEED RPM:</b>		MIN. ....	MAX. ....		
<b>WEFT DENSITY /CM:</b>		MIN. .... PPCM	MAX. .... PPCM	<b>/INCH:</b> MIN. .... PPI	MAX. .... PPI
<b>PREFERRED WEFT DENSITY /CM:</b>		MIN. .... PPCM	MAX. .... PPCM	<b>/INCH:</b> MIN. .... PPI	MAX. .... PPI
<b>YARN TYPE:</b>	<input type="checkbox"/> COTTON	<input type="checkbox"/> WOOL	<input type="checkbox"/> PURE SILK	<input type="checkbox"/> SYNTHETIC	<input type="checkbox"/> POLYPROPYLENE <input type="checkbox"/> other
<b>WARP COUNT:</b>		from ..... to .....			
<b>WEFT COUNT:</b>		from ..... to .....			
<b>N° OF WARP ENDS:</b>			<b>MAX. TENSION PER END cN:</b>		
<b>WEAVING PATTERN:</b>		<input type="checkbox"/> 1/1	<input type="checkbox"/> 2/1	<input type="checkbox"/> 3/1	<input type="checkbox"/> 4/1 <input type="checkbox"/> .....
<b>EXISTING WARP LET-OFF:</b>		<input type="checkbox"/> SULZER Mechanical	<input type="checkbox"/> SULZER Electronic	<input type="checkbox"/> other	
<b>WHIPROLL:</b>		<input type="checkbox"/> NORMAL		<input type="checkbox"/> WITH TORSION BAR	
<b>DIFFERENTIAL:</b>		<input type="checkbox"/> WITH		<input type="checkbox"/> WITHOUT	
<b>No. PINION TEETH:</b>		<input type="checkbox"/> ..... only for G6100/G6200			
<b>No. W. BEAM WHEEL TEETH:</b>		<input type="checkbox"/> .....			
<b>SCREW/SPROCKET RATIO:</b>		<input type="checkbox"/> 1:48 for F2000/F2001		<input type="checkbox"/> 1:117 for G6100/G6200	
<b>WARP BEAM FLANGE MM:</b>		<input type="checkbox"/> 600	<input type="checkbox"/> 700	<input type="checkbox"/> 800	<input type="checkbox"/> 940 <input type="checkbox"/> 1000
<b>BEAM BARRELL MM:</b>		<input type="checkbox"/> 140	<input type="checkbox"/> 150	<input type="checkbox"/> 216	<input type="checkbox"/> 262 <input type="checkbox"/> 270