

TECHNICAL SPECIFICATIONS FOR **ERGODRIVE** LET-OFF INSTALLATION  
**SOMET loom specs**

CUSTOMER: .....  
.....  
.....  
.....

AGENT: .....  
.....  
.....  
.....

LOOM: **SOMET**

YEAR: .....

SERIAL N°: .....

TYPE:		VERSION:		LOOM WIDTH:		
<input type="checkbox"/> MASTER SM92	<input type="checkbox"/> Tappet cams	<input type="checkbox"/> 190	<input type="checkbox"/> 200	<input type="checkbox"/> 210		
<input type="checkbox"/> MASTER SM93	<input type="checkbox"/> Dobby	<input type="checkbox"/> 220	<input type="checkbox"/> 230	<input type="checkbox"/> 240		
<input type="checkbox"/> THEMA	<input type="checkbox"/> Automatic dobbie	<input type="checkbox"/> 250	<input type="checkbox"/> 260	<input type="checkbox"/> 270		
	<input type="checkbox"/> Jacquard	<input type="checkbox"/> 280	<input type="checkbox"/> 290	<input type="checkbox"/> 300		
		<input type="checkbox"/> 320	<input type="checkbox"/> 330	<input type="checkbox"/> 340		
		<input type="checkbox"/> 360	<input type="checkbox"/> 380	<input type="checkbox"/> 400		
<b>3PH POWER SUPPLY:</b>		..... V	<input type="checkbox"/> 50 Hz	<input type="checkbox"/> 60 Hz		
<b>LOOM SPEED RPM:</b>		MIN. ....	MAX. ....			
<b>WEFT DENSITY /CM:</b>		MIN. .... PPCM	MAX. .... PPCM	<b>/INCH:</b>	MIN. .... PPI	MAX. .... PPI
<b>PREFERRED WEFT DENSITY /CM:</b>		MIN. .... PPCM	MAX. .... PPCM	<b>/INCH:</b>	MIN. .... PPI	MAX. .... PPI
<b>YARN TYPE:</b>	<input type="checkbox"/> COTTON	<input type="checkbox"/> WOOL	<input type="checkbox"/> PURE SILK	<input type="checkbox"/> SYNTHETIC	<input type="checkbox"/> POLYPROPYLENE	<input type="checkbox"/> other
<b>WARP COUNT:</b>		from .....	to .....			
<b>WEFT COUNT:</b>		from .....	to .....			
<b>N° OF WARP ENDS:</b>		<input type="checkbox"/>	<b>MAX. TENSION PER END cN:</b>		<input type="checkbox"/>	
<b>WEAVING PATTERN:</b>		<input type="checkbox"/> 1/1	<input type="checkbox"/> 2/1	<input type="checkbox"/> 3/1	<input type="checkbox"/> 4/1	<input type="checkbox"/> .....
<b>EXISTING WARP LET-OFF:</b>		<input type="checkbox"/> Mechanical	<input type="checkbox"/> SOMET	<input type="checkbox"/> other		
<b>WHIPROLL:</b>		<input type="checkbox"/> NORMAL	<input type="checkbox"/> .....			
<b>DIFFERENTIAL:</b>		<input type="checkbox"/> WITH	<input type="checkbox"/> WITHOUT			
<b>No. PINION TEETH:</b>		<input type="checkbox"/> 12	<input type="checkbox"/> 16	<input type="checkbox"/> 24	<input type="checkbox"/> .....	
<b>No. W. BEAM WHEEL TEETH:</b>		<input type="checkbox"/> 83	<input type="checkbox"/> 137	<input type="checkbox"/> 153	<input type="checkbox"/> .....	
<b>SCREW/SPROCKET RATIO:</b>		<input type="checkbox"/> 1:60	<input type="checkbox"/> .....			
<b>WARP BEAM FLANGE MM:</b>		<input type="checkbox"/> 600	<input type="checkbox"/> 700	<input type="checkbox"/> 800	<input type="checkbox"/> 940	<input type="checkbox"/> 1000 <input type="checkbox"/> 1016
<b>BEAM BARRELL MM:</b>		<input type="checkbox"/> 140	<input type="checkbox"/> 150	<input type="checkbox"/> 160	<input type="checkbox"/> 190	<input type="checkbox"/> 216 <input type="checkbox"/> 270